



 POLARIS


PROTECTIVE FILMS

 POLARIS PROTECTIVE FILMS FOR
SMARTPHONE

 POLARIS PROTECTIVE FILMS FOR
TABLETS AND SMART TV



POLARIS

Dental Implant System 

GC, Dental Implant System

POLARIS

Finds the Way...

Introduction	2
Standards	4
Philosophy behind Polaris	6
Macro-mechanics	6
Micro-mechanics	8
Critical Exercises	11
Portfolio	14
Closure	14
Appendices & Auxiliaries	18
Surgical Plan	27

Introducing the Implant Project

This company started a road plan of "Manufacturing the Group of Dental Implant Products" in 2016 and localized the knowledge of manufacturing this product with the help of the educated youth and scientific cities and transferred technology from the top companies in the world. The company applied the invaluable plan in the field of health industry in 2020 through employing the world's labor and the most advanced equipment and machine and European raw materials and by supplying the specialized installations and infrastructure equipment, implementing international systems and technical standards, and through effective cooperation with the accredited international universities and international reference laboratories. The company's portfolio includes a broad spectrum of the group of equipment and materials in the field of dentistry and dental prosthetics. It will be improved by introducing this new product and the company will get one step closer to its main goal, which is supplying the dental technology and necessary requirements to its fullest extent.

Dental implant surgery has emerged as a highly effective and reliable solution for replacing the roots of missing natural teeth, with success rates exceeding 95% over 10 years in clinical studies. This proven track record has led to a significant increase in the adoption of implantology worldwide, making it the gold standard for tooth replacement.

The success of an implant system depends on several critical factors, including the design of the implant's external surface, the type of connection, the coating technology, the shape of prosthetic components, and the position of the vaginal lip. Here, we provide a detailed overview of the Polaris B&P portfolio, a comprehensive and innovative solution designed to meet the highest standards in dental implantology, ensuring optimal outcomes for both clinicians and patients.



Standards





REGULAR

Connections:
Double Morse III[®]
Hex: 2.5
M2 Thread

Platform/Finishing Mechanical Features

- Hex feature design with optimized chamfered transition
- Soft tissue finish
- Maximized thread engagement

Material

- Titanium alloy
- Titanium alloy with hydrophilic coating

Hybrid Design

- Special type

Cutting Edge

- Cutting edge
- Chamfering

Our portfolio includes implants in Narrow and Regular lines, with the Regular line also featuring short implants for smaller clinical applications. Additionally, a Wide line will soon be introduced, maintaining the same connection type as the Regular line for consistency and ease of use. The Narrow line features a 1.7 mm hex, while the Regular line is designed with a 2.5 mm hex, ensuring precision and adaptability for a wide range of clinical scenarios.

NARROW

Connections:

Morse IT[®]

Hex: L7

MLA Thread

Coronal

Wide internal tapered structures
 favor the strong
 Institute of Technology,
 Massachusetts Institute


Straight Body

Tapered Apex

Micro-voids with fibrous
 structure in both zones



To complement our implant systems, we offer a comprehensive range of prosthetic components designed to meet diverse clinical needs. Our portfolio includes standard prosthetic parts, digital solutions for streamlined workflows, and customized elements tailored to individual patient anatomy for optimal aesthetics and functionality.



Enhanced tissue integration: The porous test surface promotes tissue integration through increased cell adhesion and bone formation around the implant.

Surface roughness (R_a and R_z parameters): The treatment creates both macro and micro roughness on the implant surface. The roughness increases the surface area and energy, which helps in better bone-implant contact (BIC). The surface allows for better mechanical interlocking with the bone, enhancing the primary stability of the implant.

Reduced healing time: The porous test surface shows a shorter healing period. The optimized surface topography allows bone cells to colonize the implant more quickly and accelerates the healing process and reduces surface coating.

Increased durability/hydrophobicity: The test surface improves the wettability of the implant, which enhances the contact between the implant and the biological environment, further supporting osseointegration.

5.2.2 SURFACE

Surface morphology of the substrate



What we are looking for from the manufacturer's viewpoint is the best surface in different contact area or to create proper morphology for well cell penetrating smaller nanoparticles such as 500s indicate the effect of condition and higher nanoparticles show the good effect of thermal treatment. Most of the results found are similar to those in this because the conditions are different in the different media.

State-of-the-Art Manufacturing Infrastructure

The foundation of high quality medical implants manufacturing is a structured infrastructure and process design process. This facility will be constructed to modern manufacturing best practices with cutting edge technology to ensure the highest standards of accuracy, consistency, and reliability throughout the production process. Critical systems for process monitoring, a highly accurate measurement system for quality control, and a certified machine for optimal surface texture. Additionally we employ a semi-robotic surface treatment process to enhance implant bio-compatibility and performance. To ensure the utmost hygiene and sterility our manufacturing takes place in a certified cleanroom environment, ensuring that every implant meets stringent international standards. The robust infrastructure enables a modular system that is not only flexible within the facility but also allows to meet the diverse needs of clinicians and patients worldwide.



Critical Properties of Dental Implants



The success of dental implants hinges on their fundamental aspects: physical properties, chemical properties and cellular response. The physical properties, such as surface texture, shape, roughness, hydrophobicity and mechanical strength, ensure the implant can withstand functional loads and integrate seamlessly with surrounding bone.

From the chemical properties viewpoint, the implant material must exhibit high biocompatibility and inherent resistance to prevent cellular reactions in the biological environment.

Most importantly, the cellular response to the implant—its ability to foster osseointegration and material integration—plays a pivotal role in successful outcomes, ensuring stable and long-lasting integration with the patient. By optimizing these properties using the results of SEM, cell adhesion, SEM and cell differentiation tests, we create implants that not only perform reliably but also promote natural healing and osseointegration.





Product Labeling

- Double-leafing
- Including initiation capsule & filter paper
- Crystallization instructions



Lot number



Reference code



No freezing or gentle warming



No further supply date



For single use only



Read instruction carefully



Temperature increase



Keep away from heat



Keep away from water



Performance



- Please tear open the package to release the impact from the capsule.

BLP Implant



Wisely Chosen, Simply Done...

Feature Length	Feature Diameter									
	Nominal (mm) (1)			Regulated (1)				Wildered (1)		
	Ø1.2	Ø1.3	Ø1.4	Ø1.2	Ø1.3	Ø1.4	Ø1.5	Ø1.3	Ø1.4	
L=0.1						☒	☒	☒	☒	☒
L=0.2	☒	☒	☒	☒	☒	☒	☒	☒	☒	☒
L=0.3	☒	☒	☒	☒	☒	☒	☒	☒	☒	
L=0.4	☒	☒	☒	☒	☒	☒	☒	☒		
L=0.5	☒	☒	☒	☒	☒	☒	☒			








Prosthetics & Auxiliaries



Wisely Chosen, Simply Done...

Prosthetic Diagram



Cover Screw

Typical Area
Minimum Area: 100mm²



- Requirements for Cover Screw Material:
1. High Strength
 2. High Corrosion Resistance
 3. High Temperature

Healing Abutment

Typical Area
Minimum Area: 100mm²

- **Orange**
- **Green**



10mm 10mm 10mm 10mm 10mm 10mm



10mm 10mm 10mm 10mm 10mm 10mm



Impression Coping Pickup



Impression Coping Transfer



Type	Material	Length	Ø
Anguloline			
Pickup	Steel	4.5	10.0
	Steel	6.0	10.0
Coping	CP PL 4070	4.5	10.0
	CP PL 4070	6.0	10.0
Transfer	CP PL 4085	4.5	10.0
	CP PL 4085	6.0	10.0
Coping	CP PL 4070	4.5	10.0
	CP PL 4070	6.0	10.0
Non Anguloline			
Pickup	Steel	4.0	10.0
	Steel	6.0	10.0
Transfer	CP PL 4080S	4.0	10.0
	CP PL 4080S	6.0	10.0

Straight Mounting Cementable



Accessories for the straight mounting cementable

Accessories	Ø	100	100	100	100
202-01	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
202-02	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
202-03	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
202-04	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
202-05	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
202-06	0.4	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020

Accessories for the straight mounting cementable

Accessories	Ø	100	100	100	100
212-010	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
212-011	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
212-012	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
212-013	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
212-014	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
212-015	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020
212-016	0.2	SP10C-0020	SP10C-0020	SP10C-0020	SP10C-0020



Angled Shovel and Convertible



Technical Specifications

Model	Capacity (m³)	Angle			
		15°	30°	45°	60°
SH-15	1.5	Available	Available	Available	Available
SH-30	1.5	Available	Available	Available	Available

Model	Capacity (m³)	Angle			
		15°	30°	45°	60°
SH-15	1.5	Available	Available	Available	Available
SH-30	1.5	Available	Available	Available	Available
SH-45	1.5	Available	Available	Available	Available
SH-60	1.5	Available	Available	Available	Available
SH-15	1.5	Available	Available	Available	Available
SH-30	1.5	Available	Available	Available	Available



SH-15
SH-30



SH-45
SH-60

UCLA Abutment



Temporary Abutment




Ball Abutment



Prosthetic Diagram

Ball Anklefoot Prosthesis



Pre-Milled Abutment

Model	Top View	Dimension	Part Code
Acute	Hexagon	10	090001-000
Acute	Hexagon	12	090002-000
Acute	Hexagon	14	090003-000

Model	Top View	Dimension	Part Code
Acute	Regular	10	090004-00
Acute	Regular	12	090005-00
Acute	Regular	14	090006-00



Acute Body

Model	Top View	Part Code
Acute	Hexagon	090007-000
Acute	Regular	090008-00



Tall Base

Model	Top View	Part Code
Acute	Hexagon	090009-000
Acute	Regular	090010-00





Surgical Plan

simple & friendly

PMMA/PTFE Surgical Kit



BLT Co-III

Hardening with 60 Rockwell

Sharp drill with 1 Flute

Coated with BLT III

Life length up-to 200 surgeries





Biological Processes

Lightweight expanded aggregate (LEA) or
lightweight aggregate (LWA)



Lightweight
concrete (LWC)

Lightweight
concrete (LWC)



Lightweight expanded aggregate (LEA) or
lightweight aggregate (LWA)



Lightweight
concrete (LWC)

Lightweight
concrete (LWC)

